

**QUIKRETE**<sup>®</sup>**CEMENT & CONCRETE PRODUCTS™**

## F5: Epoxies

**SAFETY DATA SHEET**  
**(Complies with OSHA 29 CFR 1910.1200)**

### SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE<sup>®</sup> Companies  
5 Concourse Parkway, Suite 1900  
Atlanta, GA 30328

Emergency Telephone Number  
INFOTRAC (800) 535-5053  
Information Telephone Number  
(800) 282-5828

SDS F5A  
Revision: Jul-18

<b>QUIKRETE<sup>®</sup> Product Name</b>	<b>Item #(s)</b>
QUIKRETE <sup>®</sup> Epoxy Concrete Repair	8620-49 (Part A)

**Product Use:** Non-sag repair epoxy

See most current revision of this document at [www.QUIKRETE.com](http://www.QUIKRETE.com).

### SECTION II - HAZARD IDENTIFICATION

#### Hazard Statements

Skin Irritant – 2  
Eye Irritant - 2B  
Skin Sensitizer - 1B  
Carcinogen - 2

#### Pictograms



**GHS Label elements, including precautionary statements**



**CEMENT & CONCRETE PRODUCTS™**

### Hazard statement(s)

May cause skin sensitization  
 Causes skin and eye irritation  
 May cause cancer  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

### Primary Route of Exposure

Eyes, skin and oral

### Carcinogenicity

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

---

## SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

---

<u>CAS Number</u>	<u>Content %</u>	<u>Chemical Name</u>
25085-99-8	60 - 80	Diglycidyl Ether of Bisphenol A
13463-67-7	0.5 – 1.5	Titanium Dioxide
Proprietary	10 - 25	Non – Hazardous Proprietary Ingredients
68460-21-9	7 - 15	Trimethylol Ethane Triglycidyl Ether

Exact concentrations have been withheld as a Trade Secret.

---

## SECTION IV – FIRST AID MEASURES

---

**Precautions:** First aid providers should avoid direct contact with this chemical. Wear protective equipment as necessary.

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.



**CEMENT & CONCRETE PRODUCTS™**

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

**Indication of immediate medical attention and special treatment needed:**

Immediately seek medical advice or attention if symptoms are significant or persist.

---

**SECTION V - FIRE FIGHTING MEASURES**

---

**Flash Point:** 149°C (>300°F)

**Flammable Limits:** N/A

**Extinguisher Media:** Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard:** None known. Thermal Decomposition can be formed.

**Special Fire Fighting Procedures:** Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

---

**SECTION VI – ACCIDENTAL RELEASE MEASURES**

---

**Personal Precautions:** Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions:** Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

---

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE**

---

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

---

**SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION**

---

**Exposure Guidelines**

Component	CAS#	OSHA	TLV
-----------	------	------	-----


**CEMENT & CONCRETE PRODUCTS™**

		<b>PEL</b>	
Titanium Dioxide	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

### Personal Protective Equipment

#### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

#### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

#### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

#### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

---

## SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

---

These data do not represent technical or sales specifications.

<b>Appearance:</b>	White Paste
<b>Evaporation Rate:</b>	N/D
<b>Odor:</b>	Slight Odor
<b>Solubility in Water:</b>	Insoluble
<b>Specific Gravity(g/cc):</b>	1.36
<b>Vapor Density(air = 1):</b>	Non-volatile
<b>Vapor Pressure:</b>	N/D
<b>VOC Content:</b>	See section 9 of part B for VOC content
<b>pH:</b>	N/D
<b>Boiling Point:</b>	N/D

---

## SECTION X – STABILITY AND REACTIVITY

---

**CEMENT & CONCRETE PRODUCTS™**

Stability: Stable

Thermal Decomposition: Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

Incompatibility: Strong acids, peroxides, and other oxidizing agents

Conditions to avoid: Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

**SECTION XI – TOXICOLOGICAL INFORMATION**

---

**Acute Oral Toxicity:**

Not Determined

**Acute Dermal Toxicity:**

Not Determined

**Acute Inhalation Toxicity:**

Not Determined

**Skin Irritation:**

Irritating to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Irritating to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

**STOT – single exposure**

Not Determined



**CEMENT & CONCRETE PRODUCTS™**

**STOT – Repeated Exposure**

Not Determined

**Carcinogenicity Classification:**

**Titanium Dioxide:**

IARC Group 2B: Possibly carcinogenic to humans.

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**SECTION XII – ECOLOGICAL INFORMATION**

**Fish:**

Diglycidyl Ether of Bisphenol A:  
Fathead minnow/LC50 (96hrs): >3.1mg/l

**Aquatic Invertebrates:**

Diglycidyl Ether of Bisphenol A:  
Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

**Algae:**

No Data Available

**Microorganisms:**

Diglycidyl Ether of Bisphenol A:  
Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

**SECTION XIII – DISPOSAL CONSIDERATIONS**

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

**SECTION XIV – TRANSPORT INFORMATION**

	<b>DOT (U.S.)</b>	<b>TDG (Canada)</b>
<b>UN-Number</b>	Not Regulated	Not Regulated
<b>UN proper shipping name</b>	Not Regulated	Not Regulated
<b>Transport Hazard Class(es)</b>	Not Regulated	Not Regulated
<b>Packing Group (if applicable)</b>	Not Regulated	Not Regulated

SDS F5A

QUIKRETE Companies, LLC

7/16/2018

---

**SECTION XV – OTHER REGULATORY INFORMATION**

---

HMIS Rating	
Health	1
Flammability	1
Physical Hazard	0
PPE	B

**NFPA Rating**

**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal RegulationsCERCLA RQ

SARA Title 311/312

Not Determined

CA Prop 65

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

TSCA

Listed or Exempt

State Regulations:

State RTK  
NJ, MA, PA

CAS#  
25085-99-8  
13463-67-7

Chemical Name  
Diglycidyl Ether of Bisphenol A  
Titanium Dioxide.

---

**SECTION XVI – OTHER INFORMATION**

---

**Last Updated: July 16, 2018**

**CEMENT & CONCRETE PRODUCTS™**

**MANUFACTURER DISCLAIMER:** This SDS to the best of our knowledge conforms to the requirements of OSHA 29 CFR 1910.1200, 91/155/EEC and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Responsibility for the product sold is subject to our standard terms and conditions, a copy of which is available upon request. This company warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, **NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT.** Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. Liability by this company for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with the proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users.

**End of SDS**



**QUIKRETE****CEMENT & CONCRETE PRODUCTS™**

## F5: Epoxies

**SAFETY DATA SHEET**  
**(Complies with OSHA 29 CFR 1910.1200)**

### SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies  
 5 Concourse Parkway, Suite 1900  
 Atlanta, GA 30328

Emergency Telephone Number  
**INFOTRAC (800) 535-5053**  
 Information Telephone Number  
 (800) 282-5828

SDS F5B  
 Revision: Jan-19

<b>QUIKRETE® Product Name</b>	<b>Item #(s)</b>
QUIKRETE® Epoxy Concrete Repair	8620-49 (Part B)

**Product Use:** Non-sag repair epoxy

See most current revision of this document at [www.QUIKRETE.com](http://www.QUIKRETE.com).

### SECTION II - HAZARD IDENTIFICATION

#### Hazard Statements

Skin Corrosion Cat 1  
 Serious Eye Damage Cat 1  
 Reproductive toxicity Cat 2  
 Skin Sensitizer Cat 1B  
 Carcinogen Cat 1

#### Pictograms



#### GHS Label elements, including precautionary statements

SDS F5B

QUIKRETE Companies, LLC

1/7/2019



**CEMENT & CONCRETE PRODUCTS™**

**Signal word**          Danger

**Hazard statement(s)**

Causes skin burns  
 Causes severe eye damage  
 Suspected of damaging fertility  
 May cause cancer  
 May be harmful if inhaled  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area  
 Avoid contact during pregnancy/while nursing

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

---

**SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

---

<u>CAS Number</u>	<u>Content%</u>	<u>Chemical Name</u>
140-31-8	5 - 15	N- Aminoethylpiperazine
112-24-3	1 – 5	Triethylenetetramine
107-21-1	1 – 5	Ethylene Glycol
84852-15-3	15 - 30	Nonylphenol
100-51-6	1 – 5	Benzyl Alcohol
90-72-2	3 - 7	Tris-2,4,6-(dimethylaminomethyl)phenol
Proprietary	10 – 20	Non – Hazardous Proprietary Ingredient
14808-60-7	0.5 – 1.5	Crystalline Silica

Exact concentrations have been withheld as a Trade Secret.

---

**SECTION IV – FIRST AID MEASURES**

---

**Precautions:** First aid providers should avoid direct contact with this chemical. Wear protective equipment as necessary.

**CEMENT & CONCRETE PRODUCTS™**

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

**Indication of immediate medical attention and special treatment needed:**

Immediately seek medical advice or attention if symptoms are significant or persist.

---

**SECTION V - FIRE FIGHTING MEASURES**

---

**Flash Point:** >93°C (200°F)

**Flammable Limits:** N/A

**Extinguisher Media:** Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard:** None known. Thermal Decomposition can be formed.

**Special Fire Fighting Procedures:** Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

---

**SECTION VI – ACCIDENTAL RELEASE MEASURES**

---

**Personal Precautions:** Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions:** Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

---

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE**

---



**CEMENT & CONCRETE PRODUCTS™**

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

## SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

### Exposure Guidelines

Component	CAS#	OSHA PEL	TLV
Ethylene Glycol	107-21-1	50ppm (Ceiling)	100 mg/ m <sup>3</sup> (Ceiling)
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.05 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>
Benzyl Alcohol	100-51-6	50ppm (Ceiling)	100 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

### Personal Protective Equipment

#### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

#### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

#### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

#### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.



**CEMENT & CONCRETE PRODUCTS™**

---

## SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

---

These data do not represent technical or sales specifications.

Appearance:	Black Paste
Evaporation Rate:	N/A
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	N/A
Vapor Density(air = 1):	Non-Volatile
Vapor Pressure:	N/A
VOC Content:	VOC <60g/L per EPA Method 24. Meets VOC requirements in all locations.
pH:	N/D
Boiling Point:	N/A

---

## SECTION X – STABILITY AND REACTIVITY

---

Stability: Stable

Thermal Decomposition: Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

Incompatibility: Strong acids, peroxides, and other oxidizing agents

Conditions to avoid: Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

## SECTION XI – TOXICOLOGICAL INFORMATION

---

**Acute Oral Toxicity:**

Not Determined

**Acute Dermal Toxicity:**

Not Determined

**Acute Inhalation Toxicity:**

Not Determined

**Skin Irritation:**

Corrosive to skin

**CEMENT & CONCRETE PRODUCTS™**

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Carcinogenicity Classification:**

Quartz Silica Sand (Crystalline Silica):

**IARC Group1:** Known human carcinogen based on human evidence.

NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.

---

**SECTION XII – ECOLOGICAL INFORMATION**

---

At the present state of knowledge, no negative ecological effects are expected. Past experiences have shown this material to have no harmful effect on the environment.

---

**SECTION XIII – DISPOSAL CONSIDERATIONS**

---

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

**SECTION XIV – TRANSPORT INFORMATION**

---

**DOT (US)**

**CARTRIDGE:** Limited Quantity, LTD QTY

**\*BULK:** AMINES, SOLID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 3259, PG III

\*Bulk packaging in quantities of 1.3 gallons (net) or less are packaged in accordance with the limited quantity exception.

**CEMENT & CONCRETE PRODUCTS™****IATA/ICAO**

**CARTRIDGE/BULK:** AMINES, SOLID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 3259, PG III

**IMDG**

**CARTRIDGE/BULK:** AMINES, SOLID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 3259, PG III

**Marine pollutant:** yes

**SECTION XV – OTHER REGULATORY INFORMATION**

HMIS Rating	
Health	*3
Flammability	1
Physical Hazard	0
PPE	B

**NFPA Rating**

**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

**Federal Regulations****CERCLA RQ**

5000 lbs

**CAS**

107-21-1

**Chemical Name**

Ethylene Glycol

SARA Title 311/312

Chronic Health Hazard

CA Prop 65

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

TSCA

Listed

**State Regulations:****State RTK**

NJ, MA, PA

**CEMENT & CONCRETE PRODUCTS™**

<u>CAS#</u>	<u>Chemical Name</u>
107-21-1	Ethylene Glycol
14808-60-7	Quartz Silica Sand (Crystalline Silica)
140-31-8	n-aminoethylpiperazine
14807-96-6	Hydrous Magnesium silicate

---

**SECTION XVI – OTHER INFORMATION**

---

**Last Updated: January 7, 2019**

**MANUFACTURER DISCLAIMER:** This SDS to the best of our knowledge conforms to the requirements of OSHA 29 CFR 1910.1200, 91/155/EEC and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Responsibility for the product sold is subject to our standard terms and conditions, a copy of which is available upon request. This company warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, **NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS, OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS FOR ANY PARTICULAR USE OR PURPOSE, OR THAT ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT.** Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product itself. Liability by this company for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with the proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users.

**End of SDS**