



Blacktop Repair

No. 8630-10, 8630-15

Product Description

Textured acrylic caulking material colored to match Blacktop. Used to fill 1/4" to 1/2" wide cracks in asphalt driveways.

Limitations

Do not apply when temperatures are below 50 °F (10 °C) or if rain threatens or is predicted within 12 hours.

Sizes:

QUIKRETE® Acrylic Blacktop Repair is packaged in 10 fl-oz (296 ml) caulking tubes and 5.5 fl-oz. (163 ml) squeeze bottles.

Color:

QUIKRETE® Acrylic Blacktop Repair is black to match asphalt surfaces.

TECHNICAL DATA

QUIKRETE® Acrylic Blacktop Repair is a water-resistant acrylic formula that stays flexible. It is textured to blend with blacktop surfaces, has minimal shrinkage, excellent adhesion, and is non-flammable

Directions: Surface must be clean, dry, free of grease, dust, or loose particles. Remove all loose stones and chips from the crack before filling.

(1) Cut tip of spout on angle to make a 1/4" (6 mm) to 3/8" (9 mm) hole. (2) Use cartridge in standard caulking gun. Apply by pushing cartridge tip over surface and forcing bead of Blacktop Repair deep into the crack. Apply no thicker than 3/8" (9 mm) at a time. On horizontal surfaces, deep cracks can be partially filled with sand prior to application. (3) Blacktop Repair can be tooled to smooth the surface. (4) Excess Blacktop Repair can be wiped off with a damp cloth. (5) Wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F/4°C for proper

application. (6) Do not apply if rain threatens or is predicted within 12 hours.



Caution: May cause eye, skin and respiratory irritation. Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Use only with adequate ventilation. Ingestion may cause irritation. Store between 35°F (2°C) and 100°F (38°C).

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30305. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies, Inc.

One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305
404.634.9100