Stucco Crack Repair
No. 8650-50

PRODUCT DESCRIPTION

Basic Uses: QUIKRETE® Stucco Crack Repair is a superior crack filler and sealer for repairs to vertical and horizontal stucco surfaces. The sanded acrylic formula is designed to blend in with the texture of stucco surfaces. Stucco Crack Repair provides excellent adhesion and remains flexible for durable repairs.

Color: off-white.

Packaging: QUIKRETE® Stucco Crack Repair is available in 5.5 oz (163 ml) squeeze tubes.

Coverage: 12 linear feet (3.7 M) at ¼" (6 mm) bead.

Application: Clean all dirt, dust, grease, and loose particles from the crack before filling. Cut the tip of the tube at an angle to make a 1/4"-3/8" (6-9 mm) opening. Apply by pushing tube tip over the surface and squeezing a bead of Stucco Crack Repair deep into the crack. Apply no thicker than 3/8" (9 mm) in one application. Stucco Crack Repair can be tooled to match the existing surface texture. Excess material may be wiped off with a damp cloth.

For best results, wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F (4°C) for proper application. Do not apply if rain threatens or is predicted within 12 hours. Store between 35°F and 100°F (2°C and 38°C). Protect from freezing.

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30305. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.