



Stucco Patch Pre-Mixed

No. 8650

PRODUCT DESCRIPTION

Basic Uses: QUIKRETE® Stucco Patch a ready to use stucco repair material designed to repair cracks holes or other minor defects up to 1/4" (6 mm) thick in stucco surfaces. The sanded acrylic formula is designed to blend in with the texture of stucco surfaces. Stucco Patch provides excellent adhesion and remains flexible for durable repairs. For smaller projects use QUIKRETE® Stucco Crack Repair in 5.5 oz (163 ml) squeeze tubes.

Color: off-white.

Packaging: QUIKRETE® Stucco Patch is available in 1 qt (946 ml) pails

Coverage: Approximately 3.25 sq. ft (0.3 M²) at 1/8" (3 mm) thickness.

Surface Preparation: Surface to be repaired must be clean, dry and free of loose material, grease and dirt. Vigorously remove any scaling paint with a wire brush.

Application: Stir thoroughly with a margin trowel. Apply Stucco Patch to the surface with a putty knife, broad knife or margin trowel. Spread and texture the stucco patch to match the surrounding stucco. For best results a rubber stucco float is recommended.

Cracks or holes up to 1/4" (6 mm) deep can be repaired in one application. Cracks or holes greater 1/4" (6 mm) deep require multiple layers of no more than 1/4" (6 mm) per layer. Wait 24 hours between layers.

Clean tools immediately with soapy water and scrub with a stiff fiber brush before material hardens.

Allow top layer to harden for at least 24 hours before painting. Use latex paints only.

Curing: QUIKRETE® Stucco Patch will begin to form a surface skin in about 20-40 minutes and

will become hard in about 2 hours depending on temperature, humidity and patch depth. Additional curing will continue for up to 3 days.

Precautions: Air and surface temperature must be above 50°F (10°C) for proper application. Do not apply if rain threatens or is predicted within 12 hours. Protect from freezing. Store between 35°F and 100°F (2°C and 38°C). Keep container tightly closed when not in use.

Warranty

The QUIKRETE® Companies warrant this product to be of merchantable quality when used or applied in accordance with the instructions or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of its product (as purchased) found to be defective, or at the shipping companies' option, to refund the purchase price. In the event of a claim under this warranty, notice must be given to The QUIKRETE® Companies in writing at Atlanta, GA 30305. The limited warranty is issued and accepted in lieu of all other express warranties and expressly excludes liability for consequential damages.

The QUIKRETE® Companies, Inc.

One Securities Centre
3490 Piedmont Road, Suite 1300
Atlanta, GA 30305
404.634.9100